

Total No. of Questions : 6]

SEAT No. :

P42

[Total No. of Pages : 2

APR - 17/BE/Insem - 47
B.E. (E & TC) (Semester - II)
BROADBAND COMMUNICATION SYSTEMS
(2012 Pattern)

Time : 1 Hour]

[Maximum Marks : 30

Instructions to the candidates:

- 1) *Solve Q. 1 or Q.2, Q.3 or Q.4, and Q.5 or Q.6*
- 2) *Neat diagrams must be drawn wherever necessary.*
- 3) *Figures to the right indicate full marks.*
- 4) *Assume suitable data if necessary.*

- Q1) a)** A step index fiber in air has a numerical aperture of 0.16, a core refractive index of 1.45 and a core diameter of $60 \mu\text{m}$. Determine normalized frequency for the fiber when light at a wavelength of $0.9 \mu\text{m}$. is transmitted. further. estimate the number of guided modes propagating in the fiber [6]
- b)** Explain three windows of transmission for optical fiber based on fiber attenuation characteristics. [4]

OR

- Q2) a)** Compare and contrast PIN photo diode & APD as optical detector in fiber communication. [6]
- b)** Enlist & explain any four losses in optical fiber communication system. [4]

- Q3) a)** An optical fiber system is to be designed to operate over an 8 km length without repeaters. The rise times of the chosen components are. [6]
Source: 8 nsec, fiber (inter modal):5ns/km.
Fiber (intra modal): 1nsec/km, detector: 6 nsec.
Estimate the maximum bit rate that may be achieved on the link when using an NRZ format and RZ format.
- b)** Write a short note on long haul system. [4]

P.T.O

OR

- Q4) a)** Components are chosen for a digital optical fiber link of overall length 7km, 20 Mbps data rate and Rz code. An LED emitting at $0.85 \mu\text{m}$ is capable of launching an average of $100 \mu\text{w}$ of optical power. (Including connector loss). A graded index fiber of $50 \mu\text{m}$ core diameter is chosen. The fiber has attenuation of 2.6 dB/km and requires splicing every kilometer with loss of 0.5 dB/splice . There is also a connector loss at receiver of 1.5 dB . Receiver requires mean incident optical power of -41 dBm for necessary BER of 10^{-10} , safety margin of 6 dB will be required. Write down the optical power budget for the system and hence determine its viability. [6]
- b) Define the following terms with respect to photo detector. [4]
- i) Responsivity
 - ii) Quantum Efficiency

- Q5) a)** A 2×2 biconical tapered fiber coupler has an i/p optical power $P_o=300 \mu\text{w}$. The o/p powers at the three other ports are $P_1=150 \mu\text{w}$, $P_2=65 \mu\text{w}$ & $P_3=8.3 \text{ nw}$. [6]

Calculate coupling ratio (splitting ratio), excess loss insertion loss and cross talk for the coupler.

- b) Explain working principle of FBG [4]
- OR

- Q6) a)** Explain working principle of EDFA [6]
- b) Explain working of optical circulator based on FBG principle [4]

